





## AD-S10T
2-way Passive Loudspeaker, 10", 250W

G2B No. **22760502**

## AD-S12
2-way Passive Loudspeaker, 12", 300W

G2B No. **22760501**

## AD-S112sw
Passive Subwoofer, 12", 300W

- IP54 방수/방진 등급
- 전 객석에 평탄한 주파수 커버리지를 제공하는 DMT™ 기능
- 특허인 X-Mount 기술로 스피커를 쉽게 설치하고, 시간이 흐르면서 미끄러지는 일이 없도록 다양한 각도로 배치 가능

| | AD-S10T | AD-S12 | AD-S112sw |
|---|---|---|---|
| Effective frequency range | 50 - 19kHz | 52 – 20kHz | 30 - 135 Hz |
| Rated noise power / voltage | 250W / 45V (rms) | 300W / 50V (rms) | 300W / 50V (rms) |
| Rated Sensitivity | 92dB, 1W@1m | 95dB, 1W@1m | 90dB, 1W@1m |
| Coverage angle (-6 dB) | 90° Conical DMT | 75° Conical DMT | |
| Maximum peak SPL | 122dB | 126dB | 121dB |
| Rated impedance | 8Ω | 8Ω | 8Ω |
| Transformer Taps (70 V) | 100, 50, 25, 12.5W and 8Ω Bypass | | |
| Transformer Taps (100 V) | 100, 50, 25W and 8Ω Bypass | | |
| HF transducer | 1″ exit / 1.4″ voice-coil compression driver | 1″ exit / 1.4″ voice-coil compression driver | |
| LF transducer | 10″ Weather Resistant Paper Cone Woofer, 2.5″ / 64mm Voice-coil | 12″ Weather Resistant Paper Cone Woofer, 3″ / 76mm Voice-coil | 12″ weather resistant paper cone woofer, 2.5″ / 64 mm voice coil |
| Dimensions (H x W x D) | 516 x 318 x 298mm | 594 x 354 x 323mm | 594 x 354 x 323mm |
| Net Weight | 15kg | 16kg | 13.2 kg |



**M10 Kit-C**
M10 forged-shoulder steel eyebolt kit