K.2 Series | Powered Loud & Stage Monitor Speaker NEW

QSC

6 YEAR WARRANTY with Product Registration

6년 워런티 적용!
(QSC 홈페이지 등록시에 한함)

K8.2

K10.2

K12.2

	K8.2	K10.2	K12.2
	Powerd Loud & Stage Monitor Speaker 8”, 2000W	Powerd Loud & Stage Monitor Speaker 10”, 2000W	Powerd Loud & Stage Monitor Speaker 12”, 2000W

- 고성능 우퍼 및 압축 드라이버
- 정교하게 조화된 2000W 전력 모듈 장착
- 라우드 스피커, 스테이지 모니터 스피커, 악기연주용, 음성 전달용 등으로 여러 이벤트 진행시 활용

Frequency Response (-6 dB)	59 Hz - 20 kHz	56 Hz - 20 kHz	50 Hz - 20 kHz
Frequency Range (-10 dB)	55 Hz - 20 kHz	50 Hz - 20 kHz	45 Hz - 20 kHz
Nominal Coverage (-6 dB)	105° Axisymetric	90° Axisymetric	75° Axisymetric
Output (Peak SPL @ 1M)	128 dB	130 dB	132 dB
Amplifier Power (Peak)	LF: 1800 W peak Class D HF: 225 W Class D	LF : 1800 W peak Class D HF: 225 W Class D	LF: 1800 W peak Class D H: 225 W Class D
Driver Information	LF: 8" cone transducer HF: 1.4" titanium compression driver	LF: 10" cone transducer HF: 1.4" titanium compression driver	LF: 12" cone transducer HF: 1.4" titanium compression driver
Dimensions (H x W x D)	449 x 280 x 269 mm	519 x 320 x 300 mm	602 x 356 x 350 mm
Net Weight	12.2 kg	14.5 kg	17.7 kg

Accessories

Carrying Tote

Outdoor Covers

Yoke Mount

Eyebolt Kit

Pole Extension

Lock Out cover