TSC-47w-G2
TSC-55w-G2



TSC-80w-G2
TSC-116w-G2





TSC-80t-G2 / TSC-116t-G2 악세사리를 추가하여 Table top 모델인 TSC-80w-G2 / TSC-116w-G2로 만들 수 있음 (TSC-47w-G2, TSC-55w-G2는 불가능)

NEW

TSC-47w-G2 TSC-55w-G2 TSC-80w-G2 TSC-116w-G2

- LCD 터치 표면 : IPS (평면전환) 기술 적용
- 고해상도 디스플레이 : 960x540 400 Nits (밝기) 픽셀
- PoE (Power over Ethernet) 지원
- 범용 마운팅 옵션 : 미국 표준 및 유럽식 벽 및 접합 박스에 장착할 수 있는 부속품 포함
- 세로 또는 가로 방향으로 작동하는 기능
- 완벽한 설계 자유 : Q-SYSDesigner 소프트 웨어에는 운영자의 편의를 반영한 UCI (사용자 제어 인터페이스) 툴 포함

Panel Type	In-Wall Touch Screen Controller	In-Wall Touch Screen Controller	In-Wall Touch Screen Controller	In-Wall Touch Screen Controller
LCD Luminance Resolution	4.7", IPS LCD 400 nits, 960 x 540 pixels	5.5", IPS LCD 400 nits, 1280 x 720 pixels	8.0", IPS LCD 400 nits, 1280 x 800 pixels	11.6", IPS LCD 350 nits, 1920 x 1080 pixels
Control Surface	4.7" capacitive touch surface	5.5" capacitive touch surface	8.0" capacitive touch surface	11.6" capacitive touch surface
Q-SYS Network LAN A	LAN (PoE) (1000 Mbps)	LAN (PoE) (1000 Mbps)	LAN (PoE) (1000 Mbps)	LAN (PoE) (1000 Mbps)
Optional External Power Source (not included)	- 12VDC @ 1A (12W) - Barrel connector : Negative contact - 5mm OD Positive contact - 2.5mm ID	- 12VDC @ 1A (12W) - Barrel connector : Negative contact - 5mm OD Positive contact - 2.5mm ID	- 12VDC @ 1A (12W) - Barrel connector : Negative contact - 5mm OD Positive contact - 2.5mm ID	- 12VDC @ 1A (12W) - Barrel connector : Negative contact - 5mm OD Positive contact - 2.5mm ID