

UBERPA**UBERPA** PORTABLE RECHARGEABLE BLUETOOTH® PA SYSTEM**NEW**

Power Output	50 Watts peak, (25 Watts continuous power)
LF Driver	6.5-inch (165.1 mm) woofer
HF Driver	1-inch (25.4 mm) tweeter
Frequency Response	90 Hz - 20 kHz
Connectors	Line/Mic channels with XLR-¼-inch (6.35 mm) TRS combination input, 1/8-inch (3.5 mm) TRS/stereo Aux input, ¼-inch (6.35 mm) Line-Out, IEC AC power connection with Mains Fuse
Charge Port	USB +5V, 1A
Indicators	Power On, battery level, Bluetooth® pairing status
Bluetooth® Connection	Manual pairing or NFC
Battery Life	50 hours of continuous use
Dimensions (HxWxD)	350 x 411 x 237 mm
Weight	8.12 kg

MIXPACK 10**MIXPACK10** All-in-one Portable System

Loudspeaker	
LF Driver	10" Woofer, 1.5" voice coil
HF Driver	1" compression driver, 1.5" voice coil
Amplifier	Class D, 400 Watts Peak
Frequency Response(-6dB)	68 Hz - 20 KHz
Crossover Frequency	2.2 KHz
Max SPL	113 dB at 1m
Mixer	
Input	Mono 4, Stereo 2
Output	Main L/R, Monitor, Record
EQ	2band per channel EQ

TROUPER**TROUPER** Compact High-performance PA System

LF Driver	3x6 ½" Woofers with 1" voice coil
HF Driver	1" voice coil Neodymium compression driver
Amplifier	Bi-amp, 200 Watts Peak (130W LF + 70W HF)
Frequency Response(-3dB)	65 Hz - 20 KHz
Crossover Frequency	1.8 KHz
Max SPL	117 dB at 1m
Dimensions (HxWxD)	741 x 212 x 257 mm
Net weight	10.2 kg

SXM 112A**SXM112A** 800-Watt 12-Inch 2-Way Powered Stage Monitor

LF Driver	12" Coax Woofer, 2" voice coil
HF Driver	1" Neodymium Driver, 1" voice coil
Amplifier	800 Watts Peak (670W LF + 130W HF)
Horn Coverage H° x V°	70°H x 70°V
Max SPL	118 dB at 1m
Dimensions (HxWxD)	313 x 393 x 513 mm
Net weight	11.85 kg